



Detailed Specifications



CopyCentre C32 Color.



CopyCentre C40 Color shown with  
Optional Duplex Automatic Document  
Feeder and Optional Two-Tray Module.

	CopyCentre™ C32 Color Digital Copier		CopyCentre™ C40 Color Digital Copier	
<b>OUTPUT SPEED</b>	<b>Black-and-white</b>	<b>Color</b>	<b>Black-and-white</b>	<b>Color</b>
	32 images per minute (ipm) letter (8.5 x 11"/216 x 279 mm/A4)	16 ipm letter	40 ipm letter (8.5 x 11"/216 x 279 mm/A4)	22 ipm letter
	20 ipm legal (8.5 x 14"/216 x 356 mm)	11 ipm legal	24 ipm legal (8.5 x 14"/216 x 356 mm)	13 ipm legal
	17 ipm ledger (11 x 17"/279 x 432 mm/A3)	9 ipm ledger	20 ipm ledger (11 x 17"/279 x 432 mm/A3)	11 ipm ledger

**CopyCentre™ C32/C40 Color**

<b>COPYING</b>	
<b>Document Scanner</b>	Duplex Automatic Document Feeder (optional) with 50-sheet capacity
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 9,999
<b>Resolution</b>	600 x 600 dpi
<b>Concurrency</b>	Concurrent scanning and copying
<b>Digital Imaging</b>	AutoIQ automatic digital image quality control Auto rotation 180° or 270° when needed Image shift Edge erase Auto centering Original type selection (photo/text, photo, text, map, inkjet, highlighted) Lighter/darker Background suppression Contrast Sharpness Screening Negative image Mirror image

Continued





## CopyCentre™ C32/C40 Color Digital Copiers

COPYING *Continued*

<b>Copy Pre-collation Memory</b>	256 MB RAM plus 18 GB hard disk drive
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
<b>Special Features</b>	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up—up to six columns by six rows Transparency dividers Covers insertion (front only, front and back, back only; blank or printed) Build Job (produce multiple sets from stored job segments) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Context-sensitive help screens Negative image Mirror image
<b>Foreign Device Interface (optional)</b>	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
<b>USB Port</b>	PC interface for upload/download of internal auditor data
<b>Accessibility Option</b>	Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features

## PAPER HANDLING—Duplex Automatic Document Feeder (optional)

<b>Capacity*</b>	50 sheets
<b>Speed</b>	32 ipm/8.5 x 11"/216 x 279 mm long edge feed (LEF)
<b>Paper Sizes Sensed</b>	Statement/5.5 x 8.5"/140 x 216 mm/A5 long edge feed (LEF) or short edge feed (SEF) Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF Legal/8.5 x 14"/216 x 356 mm SEF Ledger/11 x 17"/279 x 432 mm/A3 SEF 8 x 10"/182 x 257 mm/B5 SEF
<b>Weights</b>	16 to 32 lb bond/60 to 120 gsm

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.



## CopyCentre™ C32/C40 Color Digital Copiers

## PAPER HANDLING—Bypass Tray

<b>Capacity*</b>	100 sheets
<b>Sizes</b>	4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm/SRA3
<b>Weights</b>	16 lb bond to 110 lb index/60 to 220 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined) Lightweight Heavyweight Envelopes

## PAPER HANDLING—Front-Loading Paper Tray (standard)

<b>Tray 1</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined)

## PAPER HANDLING—INPUT TRAY OPTIONS—One Tray with Stand Option

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	1,140 sheets (Includes Tray 1, Tray 2 and Bypass Tray)

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.



## CopyCentre™ C32/C40 Color Digital Copiers

## PAPER HANDLING—INPUT TRAY OPTIONS—Three Tray Option (Tray One and Two plus Two-Tray Module)

<b>Tray 2 – Tray 4</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

## PAPER HANDLING—INPUT TRAY OPTIONS—High-Capacity Feeder Option (Tray One and Two plus High-Capacity Feeder)

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Tray 3 and Tray 4</b>	2,000 sheets
<b>Sizes</b>	8.5 x 11", B5, A4
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	3,140 sheets (Includes Tray 1, Tray 2, High-Capacity Feeder and Bypass Tray)

## PAPER HANDLING—Convenience Stapler Option

<b>Capacity*</b>	Up to 50 sheets (5,000 staples per cartridge)
------------------	---

## OUTPUT OPTIONS—Center Tray

<b>Stacking Tray</b>	400 sheets (200 sheets with finisher option)
<b>Sizes</b>	4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm/A3

## OUTPUT OPTIONS—Office Finisher

<b>Stacking Tray</b>	1,000 sheets
<b>Sizes</b>	8 x 10"/B5 to 11 x 17"/A3
<b>Weights</b>	17 to 28 lb bond/60 to 105 gsm
<b>Stapling</b>	Single (any corner) and dual Auto stapling (50 sheets maximum) Letter, legal, 11 x 17", A3, A4, B4 and B5 sizes supported

\*Paper capacities are based on 20 lb bond/75 gsm stock; capacities will vary with different weight stocks.



CopyCentre™ C32/C40 Color Digital Copiers

**ACCOUNTING**

**Internal Auditron**

Tracks and limits black and color copy usage; supports up to 2,000 user accounts or 300 general accounts  
Auditron report printout

Note: Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software.

CopyCentre™ C32 Color

CopyCentre™ C40 Color

**AVERAGE MONTHLY VOLUME**

Recommended: 4,000 to 21,000  
Duty Cycle: up to 80,000

Recommended: 8,000 to 30,000  
Duty Cycle: up to 100,000

CopyCentre™ C32/C40 Color

**BASIC CONFIGURATIONS\***

Digital Copier with platen cover, two paper trays, stand and center output tray

Note: Duplex Automatic Document Feeder, Two-Tray Module and High-Capacity Feeder are available with all configurations

**ACCESSORY OPTIONS**

- Office Finisher (50-sheet stapling)
- Foreign Device Interface
- Image Overwrite Security
- Convenience Stapler
- Xerox Copier Assistant™ Software (assistive software for the visually impaired or for persons with limited dexterity or mobility)

**ELECTRICAL REQUIREMENTS**

110–127 V Nominal, 60 Hz, 15A or  
220–240 V Nominal, 50 Hz, 10A

CopyCentre™ C32 Color

CopyCentre™ C40 Color

**POWER CONSUMPTION**

<b>Running</b>	< 540 watts	< 540 watts
<b>Standby</b>	< 192 watts	< 192 watts
<b>Low-Power Mode</b>	< 128 watts	< 159 watts
<b>Sleep Mode</b>	< 15 watts	< 15 watts
<b>Warm-up</b>	3 minutes (maximum)	3 minutes (maximum)
<b>Low-Power Recovery</b>	30 seconds (maximum)	30 seconds (maximum)

\*Features, configurations and options may vary by location.



## CopyCentre™ C32/C40 Color Digital Copiers

## ENVIRONMENTAL CONSIDERATIONS

<b>Required Temperature Range</b>	50° to 90° F (10° to 32° C)
<b>Required Relative Humidity</b>	10% to 85%
<b>Heat Emission</b>	1,844 BTU/Hr running 656 BTU/Hr standby
<b>Noise Emission</b>	34.8 dB(A) standby 51.9 dB(A) running 55.5 dB(A) impulse

## DIMENSIONS AND WEIGHT

<b>Fully Configured</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
	53"/1,346 mm	25"/636 mm	43.9"/1,116 mm	502 lbs/274 kg

## SPACE REQUIREMENTS

	<b>Width</b>	<b>Depth*</b>	<b>Height</b>
<b>Basic Configuration Without Finisher</b>	73.5"/1,867 mm	77"/1,956 mm	78"/1,981 mm
<b>Basic Configuration With Finisher</b>	83.5"/2,121 mm	77"/1,956 mm	78"/1,981 mm

## CERTIFICATIONS

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)  
 89/336/EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950/EN 60950)  
 73/23/EEC (Europe)  
 WHQL  
 Novell® NetWare®

\*Add 31.5"/800 mm to depth if installed in a hallway.



CopyCentre™ C32/C40 Color Digital Copiers

SUPPLIES

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>	<i>Expected Yield</i>
Black Toner	6R1122	1	26,000
Cyan Toner	6R1123	1	16,000
Magenta Toner	6R1124	1	15,000
Yellow Toner	6R1125	1	16,000
Drum Cartridge	13R579	1	30,000
Fuser Cartridge	8R12904	1	100,000
Waste Toner Container	8R12903	1	30,000
Staple Cartridge (Finisher)	8R12915	3	5,000 per cartridge
Staples (Convenience Stapler)	8R7644	4	5,000 per cartridge

**Total satisfaction guaranteed.**

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox CopyCentre™ which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



**XEROX**

Worldwide Partner



© 2003 XEROX CORPORATION. All rights reserved. XEROX®, The Document Company®, the digital X®, CopyCentre and Copier Assistant are trademarks of XEROX CORPORATION. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Other marks are trademarks or registered trademarks of the companies with which they are associated. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product appearance, build status and/or specifications are subject to change without notice. Printed in U.S.A. 3/03 36 USC 220506 610P716200A